

Xtreme ViKiNG



The Viking re-deployable IR camera represents a step forward in the deployable technology that has so far been available to the police, enforcement bodies and CCTV system managers to date.

Uniquely adaptable this really is a plug and play re-deployable camera. Install the mounting plate to a wall existing pole or lighting column and just add power. The Viking unit will automatically start recording from this point and can be accessed via WLAN, GSM, PDA and/or a smart phone.

With H264 compression the standard 500Gig hard drive is sufficient to record the video image at full resolution and 25IPS for more than 31days meeting the needs of public and private sector clients. With the combination of dual inbuilt antenna's for Wi-Fi and GSM there will never be a problem with connectivity and so either covertly or overtly the deterrent will be in place immediately.

Don't worry about night time as the unit has IR as standard and will illuminate targets up to 100m away. The vandal resistant housing which is both aesthetically pleasing as well as extremely functional can be manufactured in any RAL colour you require to meet in with your needs.

There is no options list just an out of the box product that will meet every need that you may have for security or surveillance applications.

Key Features

- Easy Installation
- Fully Functioning Dome Camera
- Integrated IR as Standard
- Remote Access and Viewing
- Internal DVR
- Remote Download of Video
- Wi-Fi and GSM Connectivity
- 26x Optical Zoom
- 12x Digital Zoom
- Manufactured to IP66

Typical Applications

- ASBO's
- Covert / Overt Surveillance
- Event Management
- Trouble Hot Spots
- Parking Enforcement
- Site Security
- Fraud Investigation
- Traffic Monitoring



Xtreme ViKiNG

DVR Specification

Maximum Image Resolutions:

PAL	720x576
NTSC	720x486
Image Resolution	480TVL

Storage:

Internal	500
Back up to PC	Yes
Back up to Laptop	Yes
Back up to CF Card	Yes
Back up to USB	Yes

User Interface:

PC Remote Access Software	Yes
Smart Phone Remote Access	Yes
PDA Remote Access	Yes

Video File Compression:

Compression Format	H.264
--------------------	-------

Network Connectivity:

WLAN Via Laptop	Yes
WLAN Via Control Room	Yes
WLAN via GSM	Yes
GPRS	Yes
GPS Positioning (if Required)	Yes

Housing:

Design and Construction	IP66
-------------------------	------

General:

Secure Access	Yes
Dual Wi-Fi and GSM Aerials	Yes



Camera Specification

Camera:

Sony	1/4" CCD
TVL	460TVL
Colour Sensitivity	0.05lux
Monochrome	0.01lux
Optical Zoom	26x
Digital Zoom	12x
Focal Length	4.1-73.8mm

IR Illumination:

IR Illumination	Parametric Control
IR Wavelength	830nm
Night time Range	100m

Mechanics:

Pan Speed	200°/sec
Tilt Speed	100°/sec
Pan Angle	360° cont.
Pan Limits	Programmable
Tilt Angles	+5 to -90°
Pan/tilt to zoom ratio	Via Menu

Features:

Dynamic Privacy	24 zones
Presets	256
Preset Tours	10
Photocell	Inbuilt
Fan	Yes
Heater	Yes
Operating Temp.	-35 to +50°C

Other:

Wall Mount Kit	Yes
Pole Mount Kit	Yes
Warranty	1 Year RTB